



PACIFIC MAX POWER

20W50 ENGINE OIL

Introduction : This oil is specially formulated from high viscosity base oil for Gasoline Engine. It may be used in CNG/LPG in or Diesel vehicles also. It is blended with specially selected additives for excellent oxidation & nitration resistance.

Applications : Recommended for all Cars, Light Commercial Vehicles using CNG/LPG or Petrol/Diesel. It can also be used for 3-Wheeler Passenger & Goods Carriers.

Performance Benefits :

1. Low ash contents reduces the formation of lacquer/ sludge in the engines.
2. Good Anti-scuffing properties.
3. Protect the Engine from Nitrates & Oxide formation.
4. Long drain Period in Oil Change.

Specifications : API : SF/CD, IS-13656-2002, MIL-L-2104C

Characteristics :

SAE VG	20W50
Appearance	Clear, Bright Golden Colour
Kinematic Viscosity, cSt @100°C	18-20
Viscosity Index, min.	120
Pour Point, °C, max.	-21
Flash Point, COC, °C, min.	220

Pack Size : 210 Ltrs, 50 Ltrs, 20 Ltrs, 5 Ltrs, 3Ltrs & 1 Ltr.

Precautions :

1. Running engine with insufficient oil or improper grade of oil may cause serious damage to engine. Oil change intervals to be maintained as per engine manufacturers recommendations. Oil level to be checked before running the engine.
2. Oil properties may be lost due to overheating of engines due to failure of proper cooling system and oil to be changed if the engine is overheated abnormally.
3. Change Oil filters whenever oil is changed.

*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil