



Pacific Product Data Sheet

PACIFIC RUSTILO - 111 (RUST PREVENTIVE OIL)

Introduction : Pacific Rustilo - 111 is a dewatering fluid, containing oil soluble surface acting agent dissolved in a solvent with suitable corrosion- preventive and film forming substances. It contains selected additives which provide excellent ability to wet metal surfaces in preference to water. It can be applied at room temperature by dip or spray method. The film formed over metal surfaces can be easily removed by dipping the parts in suitable solvent.

Applications : Provides effective protection against rust during short term storage in between operations. When the work piece is dipped in Pacific Rustilo the water adhering to metal surface gets dislodged by a thin film of this oil. After the application, the solvent evaporates, leaving soft grease like protective film on the metal surface.

Performance Benefits :

1. Forms very thin protective film, which does not interfere with gauging of the work-piece dimension.
2. Provides excellent rust protection to metal surfaces during storage, in between machining operations.
3. Film formed can be removed easily with the help of a common petroleum solvent. .

Specification : IS : 1154-1957 (Revised 1990)
BIS : 7451-1992 Type TP 2 (b)

Characteristics

	PACIFIC RUSTILO 111
Kinematic Viscosity @ 40°C (Typical)	1.5
Flash Point, (Abel) °C min.	30
Copper Strip Corrosion @ 50°C, 3 hrs max	1
Emulsifying Properties, volume separated in 60 minutes in ml., min.	60
Water displacement Test IS 1154 Appendix 'A'	Pass

Pack Size : 210 Ltr & 20 Ltrs

Precautions : Usual precautions with a Solvent based product should be taken while using Pacific Rustilo.

Contact our Toll Free No. **18002122411**

*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil