



PACIFIC PRESS SUPER

PREMIUM COMPRESSOR OILS

Introduction : PACIFIC PRESS SUPER OILS are superior performance mineral oil based compressor lubricants. These specially developed air compressor oils are blended from premium quality solvent refined base stocks with carefully chosen superior performance additive package to deliver best performance to meet the stated specifications.

Application

1. Recommended for lubrication of heavy-duty reciprocating and rotary air compressors even encountering air discharge temperature up to 220°C.
2. Suitable for lubrication of reciprocating and rotary compressors as product is designed to meet OEM stipulated viscosity grade.

Performance Benefits :

1. Good lubrication even under extended high operating temperature and high load condition.
2. Exceptional thermal stability characteristics.
3. Good corrosion and rust protection properties.
4. Reduce oil consumption due to low volatility characteristics.
5. Low carbon forming and deposition tendency.
6. Trouble free starting at low temperature.
7. Minimize carbon deposits reducing risk of fire & Explosion.

Specification : ISO DIS – 6521
DIN 51506VD-L

Characteristics :

ISO VG	PACIFIC PRESS SUPER						
	32	46	68	100	150	220	320
Kinematic Viscosity, cSt @ 40°C	29-33	43-48	64-72	95-105	145-155	210 – 230	305 – 335
Viscosity Index, Min,	95	95	95	95	95	90	90
Flash Point (COC), °C Min	190	200	204	210	220	230	250
Pour Point, °C Max	(-) 9	(-) 9	(-) 9	(-) 9	(-) 3	(-) 3	(-) 3
Rust Test, (D-665 A&B, 24 hrs.)	Pass	Pass	Pass	Pass	Pass	Pass	Pass

Pack Size : 210 ltrs & 20 Ltrs.

*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil