



PACIFIC ROAD KING

20W40 CF/SF

Engine Oil

Introduction : It is high performance multigrade engine oil recommended for super charged and turbo charged diesel engines. This oil has exceptional thermal and oxidation stability and outstanding viscosity related performance to meet round the year requirement.

Applications : All types of super charged & turbo charged diesel Heavy Commercial Vehicles, Light Commercial Vehicles, Jeeps, stationary Diesel Engine & DG sets of leading vehicle manufacturers.

Performance Benefits :

1. Excellent oxidation stability
2. Engine protection against rust, corrosion, wear and deposits.
3. Longer engine life.
4. Protection against starting friction.
5. Easy cold starting & faster warm up.
6. Keeps engine clean in severe operating conditions.
7. Longer battery life.

Specifications : SAE 20 W 40 Performance Level – CF/SF

Characteristics :

Density@20°C	0.875
Colour ASTM	4
Viscosity cSt @100° C (min.)	14.50
Viscosity index	115
Flash point COC° C (min.)	205
Pour point ° C (max.)	-21
TBN mg KOH/gm	9 to 11
Sulphated Ash(Max)	1.3

Pack Size : 210 Ltrs, 55 Ltrs, 20 Ltrs, 10 Ltrs, 7.5 Ltrs, 6 Ltrs., 5 Ltrs, 1Ltr & 500 ml.

Precautions :

1. Running engine with insufficient oil or improper grade of oil may cause serious damage to engine. Oil change intervals to be maintained as per engine manufacturers recommendations. Oil level to be checked before running the engine.
2. Oil properties may be lost due to overheating of engines due to failure of proper cooling system and oil to be changed if the engine is overheated abnormally.
3. Change Oil filters whenever oil is changed.

*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil