



# PACIFIC SEWING MACHINE OIL

**Introduction :** This oil is high performance Textile Knitting & Sewing Machine Lubricant. This product is formulated with group III base oils and selected additives to enhance anti-oxidant, scour ability & anti foaming characteristics to meet the lubricants requirement of modern textile machines.

**Application :** This oil is used for all kinds of sewing machines, textile looms & machinery. It is excellent for needle mechanism of flat-bed fully fashioned nylon stocking knitting machines where sized and non-sized yarn is used. This product is equally applicable to faster & slower speeds on heavier fabrics.

**Performance Benefits :**

1. Low viscosity with light color.
2. Superior oxidation stability.
3. Good corrosion prevention properties.
4. Special non-drip properties.
5. Easy wash out & anti-stain properties which ensure stains removal.
6. Excellent anti-foam characteristics.
7. Effective surface wetting properties.
8. Good seal compatibility.

**Characteristics :**

PROPERTIES	UNITS	VALUE	TEST METHOD
ISO Grade	-	15	DIN 51 511
Specific Gravity@ 15°C	-	0.832	ASTM D-4052
Viscosity@ 40°C	mm2/s	15.0	ASTM D-445
@ 100oC	mm2/s	3.55	ASTM D-445
Viscosity Index	-	118	ASTM D-2270
Flash Point, COC	°C	170	ASTM D-92
Pour Point	°C	-25	ASTM D-97
Colour	-	<0.5	ASTM D-1500

**Pack Size :** 210 Ltrs, 20 Ltrs & 1Ltr.

\*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil