



Pacific Product Data Sheet

PACIFIC MTO- MINERAL TURPENTINE OIL

Introduction : Pacific MTO is refined water white in color, solvent of moderate volatility. It contains about 40 to 50% Aromatic hydrocarbons which provides very good solvency. It is also known as petro pine.

Applications :

1. Used as raw material for manufacturing Paints & varnishes.
2. Used as cleaning material for dry cleaning & other industrial cleaning.
3. Used as a thinner in painting
4. Used as Wood Primers.
5. Used for manufacturing Liquid shoe polish and metal treatment chemicals.
6. Used for manufacturing printing inks.

Performance Benefits :

1. It easily removes oils and greases from metal surface.
2. Due to Aromatic contents, it ensures very good solvency.
3. Fast setting power.
4. Eco friendly.

Specifications : IS: 1745-1978 (2nd Revision) / AS 1700

Characteristics :	Parameters	Value
	Color	Water White
	Sp. Gr. @ 30° C	0.78
	Kin. Visco @ 40°C cSt	>1.0 CST
	Flash Point (PMCC)°C	>45°C
	Aromatic Content	40%
	Moisture Content	0.05%
	Sulphur Content	0.50%
	Pour Point	<0°C
	Copper strip corrosion @ 50 C for 3 hrs	Not worse than 1
	Residue on evaporation (air jet), max	Mg/100 ml unit, 5 Spec.

Pack size : 210 ltr, 1.5 ltr, 1 ltr, 900 ml, 700 ml, 500 ml & 350 ml

Precautions : Class 3.1 C flammable liquid.

1. Should not be stored where temperature is above 30°C.
2. Should be stored under shed.
3. If stored in open space, drums should be laid horizontally to avoid the possible ingress of water.
4. Avoid exposure to hot sunshine.

Contact our Toll Free No. **18002122411**

*These Specifications are of a Particular Lot they can differ from lot to lot but will not effect the performance of the oil